



Hi-5

5.12 kWh



GET AWAY

FROM LOAD SHEDDING

FEATURES

1C
Continuous Power

10
Year Warranty

32
Units Stackable

- 10 year warranty
- Ultra safe LFP material
- Short circuit protection
- Flexible remote upgrade
- Wide range inverter compatibility
- Parallel up to 32 modules
- 1C rate continuous charge/discharge
- Multi protection to avoid over discharge
- Smart BMS management for longer lifespan
- Active balancing charging, low self consumption



Model	Hi-5
Cell Type	LFP
Rated Power	5.12kWh
Rated Capacity	100Ah
Rated Voltage	51.2V
Charge Voltage	56.5V
Max Charge/Discharge Current	100A
Discharge Peak Current	105A / 15s, 120A / 0.5s
Parallel	Up to 32 units paralleable w/o extra device needed, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension	481*452.6*165mm
Weight	50Kg
Communication	CAN/RS485
Compatible Inverter	Victron, Luxpower, Deye, Voltronic, SMA Goodwe, Growatt, Sofar, Solark, SRNE, Must
Humidity	5%~85% RH (No condensation)
Work Temperature	-20 °C ~ +55 °C
Storage Temperature	-10 °C ~ +35 °C
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure
Warranty *	10 year, 6000 cycles
Certification	CE UN38.3 IEC62619
Protection	Over charge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection